

Macro Twin Lite MT-26EX-RT	
Power	
Guide No. (ISO100).meters	26
Zoom	
Zoom head	No
focal length coverage	-
Coverage with wide panel	-
Auto zoom for sensor size	-
Flash modes	
Auto exposure control	E-TTLII/E-TTL/TTL
High speed sync (FP)	Yes
Manual / output settings	Yes - 1/1- 1/512
Manual steps	1/3 step
Strobe / output settings	-
Frequency	-
Video light	-
Video light power	-
Video light colour temperature	-
Flash-related function	
FE lock	Yes
Flash exposure compensation	Yes
Flash Exposure bracketing	Yes
Second-curtain flash sync	Yes
Modelling flash	Yes
Colour temperature info communication	Yes
Wireless flash	
Transmitter	Yes
Transmission type	Infra-red/ Radio
Transmitter Max range approx	Indoors: 10m Outdoors: 6m / 10m
Slave	No
No of groups	3*1 / 5
No of channels	4 / 15
Remote Shutter Release	-
Flash head movement	
Up	-
Down	-
Left	-
Right	-
AF Assist	
AF-assist beam	No (Focusing lamp)
Number of AF points supported	-
AF-assist beam type	-
Power source	
Battery	4 x AA batteries
Minimum recycling time *2	Approx. 5.5sec
External power supply	Yes - CP-E4n
Construction	
Dust and water resistance	No
Mounting foot material	Metal
Misc.	
Custom function	8 (19 options) + 5 personal functions
Flash settings from camera menus *3	Yes
External flash exposure sensor	No
PC terminal	No
Compatible Accessories	Macro Lite Adapter 72c, 67 Compact battery Pack CP-E4n EX Series Speedlite with optical or Radio Slave function
Dedicated flash bracket	No
Dimensions & weight	
Size (W x H x D), mm	Control unit 69.5 x 112.5 x 90 Flash unit 62.3 x 55.8 x 49.1
Weight (Excluding batteries), grams	570g