

Canon**XF705**

UPPLÖSNING	FÄRGSAMPLING	BIT-DJUP	BILDHASTIGHET	CODEC	Mbit/s
3840 x 2160	YCC 4:2:2	10-bitars	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.265/HEVC	160 Mbit/s/110 Mbit/s
1920 x 1080	YCC 4:2:2	10-bitars	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.265/HEVC	60 Mbit/s/45 Mbit/s
			59,94i, 50,00i		60 Mbit/s/45 Mbit/s
			120P, 100P		180 Mbit/s
3840 x 2160	YCC 4:2:0	8-bitars	29,97P, 23,98P, 25,00P	H.264/XF-AVC	160 Mbit/s
1920 x 1080	YCC 4:2:0	8-bitars	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.264/XF-AVC	45 Mbit/s
			59,94i, 50,00i	H.264/XF-AVC	35 Mbit/s
			120P, 100P	H.264/XF-AVC	45 Mbit/s
1280 x 720	YCC 4:2:0	8-bitars	59,94P	H.264/XF-AVC	180 Mbit/s
1280 x 720	YCC 4:2:0	8-bitars	59,94P	H.264/XF-AVC	8 Mbit/s
1920 x 1080	YCC 4:2:0	8-bitars	59,94P, 29,97P, 23,98P, 50,00P, 25,00P	H.264/MP4	35 Mbit/s/8 Mbit/s